

DESCRIPTION

COMETA is an acrylic emulsion based ready for use decorative paint system, having a simplicity of application and delicacy of antique look.

APPLICATION AREA

Used on wall, plaster coating, concrete and wood surfaces after surface preparation with the appropriate primer.

FEATURES

- COMETA is a decorative product for interiors, which hides uneven wall surfaces easily due to its particulate structure and toning effect,
- It is resistant to hard and long-term abrasion,
- As it is water-based, it is harmless to human health and environment,
- It provides a pleasant odor in the application environments with its perfumed feature.

SURFACE PREPARATION

- After cleaning all kinds of dirt, oil, blistered paint and dust from the application surfaces, surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and painted surfaces should be primed with SAN DECO DECOPRIMER
- After Decoprimer is diluted by volume %20-25 with clean water, it should be applied to the surface with a brush with two layers application. In between layers complete dry condition must be provided.

APPLICATION INSTRUCTIONS

- After primer completely dried, COMETA is mixed carefully with a spatula and applied by its special brush. After 25 minutes, the desired final look should be given to the surface with a plastic spatula; different decorative effects can be achieved by the technique used,
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

DRYING TIME

Allow 4-5 hours for touch dry and 24-48 hours for complete dry at 23 °C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

-1 lt covers 7,5 - 9,5 m² of surface,

-1 kg covers 6,5 - 8,5 m² of surface,

-The paint consumption for 1 m² area is 100-130 ml and 120 - 155 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight and at a temperature between +5 °C and +35 °C.

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1) May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product